

Style	Wood
Construction	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer Thickness	40 mil (1 mm)
Wear Layer	Quantum Guard Elite [®]
Edge Treatment	Micro-bevel or Unbeveled
Sizes	3" x 36" (76 x 915 mm) 9" x 36" (229 x 915 mm) 4.5" x 36" (114 x 915 mm) 7.25" x 48" (184 x 1220 mm) Xtra 6" x 36" (152 x 915 mm) 9" x 48" (229 x 1220 mm) Xtra
Colors	72
Packaging	3" x 36" - 60 pcs, 45 ft ² (4.181 m ²), 30.06 lbs (13.63 kg) 9" x 36" - 20 pcs, 45 ft ² (4.181 m ²), 30.06 lbs (13.63 kg) 4.5" x 36" - 40 pcs, 45 ft ² (4.181 m ²), 30.06 lbs (13.63 kg) 7.25" x 48" - 18 pcs, 43 ft ² (3.995 m ²), 28.72 lbs (13.03 kg) 6" x 36" - 30 pcs, 45 ft ² (4.181 m ²), 30.06 lbs (13.63 kg) 9" x 48" - 15 pcs, 45 ft ² (4.181 m ²), 30.06 lbs (13.63 kg)
Adhesive	Packaging may differ for QuickStix [®] Porous & Non-porous Substrates: Amtico PSA Full Spread, Transitional Pressure Sensitive, High Moisture Amtico RP-18 Full Spread, One Component XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray Non-porous Substrates Only: Amtico 373 Full Spread Note: Must use Amtico RP-18, XpressStep or XpressStep Premium adhesive under hospital beds and heavy rolling lead areas. Use Amtico RP-18 where higher risk of topical moisture would be a concern.
QuickStix[®]	Available with QuickStix [®] pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix [®] floors can be used immediately after installation, even in extreme moisture areas.
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance.
Testing	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class I; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
Environmental Data	
Rapidly Renewable Content	Contains 3% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
Product Declarations	EPDs, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials Visit mM Origin website, mindfulmaterials.originbuild.com , for current transparency information
mindful MATERIALS Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered
Warranty	Limited 25-Year Commercial Warranty Limited 25-Year Quantum Guard Elite [®] Wear Warranty

Crafted with Purpose.

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com